

AMENDMENTS TO THE CLAIMS

Please amend Claim 25 as follows:

1. (Original) A safety shield apparatus comprising:
- a needle having a distal portion and a proximal portion; and
- a shield including at least one elongated part, the shield having a proximal end mounted with the proximal portion of the needle and a distal end mounted with a planar contact surface, the shield being extensible between a retracted position and an extended position via fixed positioning of the planar contact surface relative to movement of the shield.
2. (Original) A safety shield apparatus according to claim 1, further comprising a needle hub configured to support the proximal portion of the needle.
3. (Original) A safety shield apparatus according to claim 2, wherein the needle hub includes an appendage.
4. (Original) A safety shield apparatus according to claim 3, wherein the appendage has at least one opening to facilitate manipulation thereof.
5. (Original) A safety shield apparatus according to claim 3, wherein the appendage has at least one wing for manipulation thereof.
6. (Original) A safety shield apparatus according to claim 1, wherein the shield includes at least one segment.
7. (Original) A safety shield apparatus according to claim 1, wherein the distal portion of the needle is angularly displaced approximately 90 degrees from the proximal portion.

- 1
B
8. (Original) A safety shield apparatus according to claim 1, wherein the planar contact surface includes a pad for engagement with a subject.
 9. (Original) A safety shield apparatus according to claim 6, wherein the segment defines a channel.
 10. (Original) A safety shield apparatus according to claim 6, wherein the segment defines a channel and the shield has a slider configured for slidable movement with the channel.
 11. (Original) A safety shield apparatus according to claim 1, wherein the shield includes a latch engageable with the needle.
 12. (Original) A safety shield apparatus according to claim 11, wherein the latch includes a latch arm for maintaining the shield in the extended position.
 13. (Original) A safety shield apparatus according to claim 11, wherein the latch includes a plurality of surfaces configured to maintain the shield in the extended position.
 14. (Original) A safety shield apparatus according to claim 11, wherein the latch includes an arcuate surface engageable with the needle.
 15. (Original) A safety shield apparatus comprising:
 - a needle having a distal portion defining a longitudinal axis which is angularly displaced relative to a longitudinal axis defined by a proximal portion of the needle; and
 - a shield mounted with the needle and extensible, via a needle guide movably guiding the needle, between a retracted position and an extended position.

16. (Original) A safety shield apparatus according to claim 15, further comprising a needle hub configured to support the proximal portion of the needle.
17. (Original) A safety shield apparatus according to claim 16, wherein the needle hub includes an appendage.
18. (Original) A safety shield apparatus according to claim 17, wherein the appendage has at least one opening to facilitate manipulation thereof.
19. A safety shield apparatus according to claim 17, wherein the appendage has at least one wing for manipulation thereof.
20. (Original) A safety shield apparatus according to claim 15, wherein the shield includes at least one segment.
21. (Original) A safety shield apparatus according to claim 15, wherein the distal portion of the needle is angularly displaced approximately 90 degrees from the proximal portion.
22. (Original) A safety shield apparatus according to claim 15, wherein a distal end of the shield is attached to a planar contact surface.
23. (Original) A safety shield apparatus according to claim 22, wherein the planar contact surface includes a pad for engagement with a subject.
24. (Original) A safety shield apparatus according to claim 15, wherein a distal end of the shield is hingedly attached to a planar contact surface.
25. (Currently Amended) A safety shield apparatus according to claim 15, wherein a distal end of the shield is releasably ~~detachably~~ attached to a planar contact surface.

26. (Original) A safety shield apparatus according to claim 24, wherein the planar contact surface includes a pad for engagement with a subject.
27. (Original) A safety shield apparatus according to claim 20, wherein the segment defines a channel.
28. (Original) A safety shield apparatus according to claim 20, wherein the segment defines a channel and the shield has a slider configured for slidable movement with the channel.
29. (Original) A safety shield apparatus according to claim 15, wherein the shield includes a latch engageable with the needle.
30. (Original) A safety shield apparatus according to claim 29, wherein the latch includes a latch arm for maintaining the shield in the extended position.
31. (Original) A safety shield apparatus according to claim 29, wherein the latch includes a plurality of surfaces configured to maintain the shield in the extended position.
32. (Original) A safety shield apparatus according to claim 29, wherein the latch includes an arcuate surface engageable with the needle.
33. (Original) A safety shield apparatus comprising:
- a needle having a distal portion defining a longitudinal axis which is angularly displaced relative to a longitudinal axis defined by a proximal portion of the needle; and
- a shield including at least one elongated part, the shield having a proximal end mounted with the proximal portion of the needle and a distal end mounted with a planar contact surface, the shield being extensible between a retracted position and an extended

position via fixed positioning of the planar contact surface relative to movement of the shield.

- B¹
34. (Original) A safety shield apparatus according to claim 33, wherein the planar contact surface includes a plurality of openings.
35. (Original) A safety shield apparatus according to claim 33, wherein the planar contact surface includes an anchor part.
36. (Original) A safety shield apparatus according to claim 33, wherein the distal end of the shield is hingedly attached to the planar contact surface.
37. (Original) A safety shield apparatus according to claim 33, wherein the planar contact surface includes a pad for engagement with a subject.
38. (Original) A safety shield apparatus comprising:
- a needle having a distal portion defining a longitudinal axis which is angularly displaced relative to a longitudinal axis defined by a proximal portion of the needle; and
- a shield means, mounted with the needle and extensible between a retracted position and an extended position, for preventing hazardous exposure to the distal portion of the needle.
39. (Original) A safety shield apparatus according to claim 38, further comprising a latch means engageable with the needle for maintaining the shield means in the extended position.
40. (Previously Added) A safety shield apparatus according to claim 1, wherein the planar contact surface includes texturing.
-